EDIFIER®

Edifier Studio®

R2000DB

RCA optical input 🅑 Bluetooth®

PRODUCT DESCRIPTION

The R2000BD features a classic design with a side panel in high glossy black finish and delivers powerful audio for a variety of applications. Using the RCA-RCA or RCA-AUX audio cables, you can connect audio devices or consoles simultaneously whether for PC, gaming consoles or mini theatre applications. The speaker set is very flexible – offering Optical. Bluetooth and dual RCA inputs for connectivity to multiple audio sources. The unit ships with a remote control that incorporates volume and STBY/Mute buttons as well as a direct source select with two pre-set EQ, Dynamic and Classic type

FEATURES

- Active bookshelf speaker with Bluetooth pairing capability for music playback
- 5 inch bass driver with Aluminum diaphragm and 1 inch tweeter driver
- Optical and dual RCA inputs for connectivity to multiple audio sources
- Class D amplifier system with Digital Signal Processing (DSP) and Dynamic Range Control (DRC)
- Wireless remote control with audio source selection, mute and volume adjustment
- Rear side panel controls bass, treble and master volume
- Side panels with high gloss piano finish
- 100% MDF wooden enclosure to minimize acoustic resonance
- Universal 100V-240V power supply

SPECIFICATIONS

Total Power Output	: 24Wx2 + 36Wx2 (DRC On)
Signal to Noise Ratio	: ≥85dB
Frequency Response	: 50Hz ~ 20 KHz (@+/-3db)
Distortion	: ≤0.5%
Channel Separation	: ≥45dB
Input Sensitivity	: LINE 1: 900±50 mV
	LINE 2: 700±50 mV
Optical	: 500±50mFFs
Audio Input	: RCA, Optical, Bluetooth
Speaker Unit	: Tweeter: 25mm Silk Dome Tweeter, Bass: 5 inch (132mm)
Dimension	: Active Speaker: 174x289x252 (mm) Passive Speaker : 174x289x238 (mm)
Weight (Net/Gross)	: Net 9.72Kg

ORDERING DETAILS

EAN:	Model No.:	Description:
6923520264346	R2000DB	2.0 Speaker System with Bluetooth and Optical Input

*All specifications are subject to change without notice

a passion for sound®

www.edifier-international.com
©2010 Edifier International Limited